

# Mobil Delvac 1330, 1340

## High Performance Diesel Engine Oils

### Product Description

Mobil Delvac 1330 and 1340 are high performance monograde diesel engine oils formulated from advanced technology base oils and a balanced additive system. They are specifically engineered for performance in naturally aspirated and turbo-charged 4-stroke diesel engines operating under severe conditions in both on-road and off-road applications. Mobil Delvac 1300 monogrades are used in a wide range of applications where a monograde lubricant is recommended.

### Features and Benefits

Features	Advantages and Potential Benefits
Excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion	Prolonged engine life Less wear Excellent protection against ring sticking
Extended TBN reserve	Long-term deposit/wear control Controls formation of acids when using higher sulfur fuels

### Applications

- Naturally aspirated and turbo-charged diesel powered equipment
- On-road light and heavy -duty trucking
- Off-road industries including: construction, mining, quarrying, and agriculture

### Specifications and Approvals

Mobil Delvac 1300 Monogrades are recommended for use in applications requiring:	Mobil Delvac 1330	Mobil Delvac 1340
API CF, CD	X	X
API CF-2, CD-II	X	X
API SL, SJ, SH	X	X
Mack EO-K/2	X	X
Allison C-4	X	
Caterpillar TO-2	X	X
Vickers 35VQ25	X	X



## Typical Properties

Mobil Delvac 1300 Mongrades	Mobil Delvac 1330	Mobil Delvac 1340
SAE Grade	30	40
Viscosity, ASTM D445		
cSt @ 40°C	102	137
cSt @ 100°C	12.0	14.3
Viscosity Index, ASTM D2270	108	102
Sulfated Ash, wt%, ASTM D874	1.0	1.0
Total Base Number, ASTM D2896	8.2	8.2
Pour Point, °C, ASTM D5949	-24	-15
Flash Point, °C, ASTM D92	238	242
Colour, ASTM D1500	3.0	3.0
Density, kg/m <sup>3</sup> @ 15°C, ASTM D4052	888	890

## Precautions

The products described on this data sheet are manufactured from high quality petroleum base stocks, carefully blended with selected additives. As with all petroleum products, good personal hygiene and careful handling should always be practiced. Avoid prolonged contact to skin, splashing into the eyes, ingestion or vapour inhalation. Please refer to the Material Safety Data Sheet for further information.

Note: The products described on this data sheet are NOT controlled under Canadian WHMIS legislation.

*Delvac is a trademark of ExxonMobil Corporation, or one of its subsidiaries. Imperial Oil, Licensee.*

05-2010