



Primol 382

Medicinal grade White Oil

Product Description

Primol 382 is a purified mixture of liquid saturated hydrocarbons. It is a colourless, transparent oily liquid and is essentially odourless and tasteless. It is obtained from petroleum through several refining stages, including an ultimate purification by catalytic hydrogenation.

Primol 382 is manufactured to exceed the purity requirements of the Pharmacopoeias. Due to its superior chemical inertness, it demonstrates better colour and oxidative stability than most mineral and vegetable oils, when stored and used under controlled conditions.

ExxonMobil White Oils are produced and controlled according to the ExxonMobil Product Quality Management System, EN ISO 9000 or equivalent standard.

Applications

Primol 382 can be used in a variety of food-related, cosmetic and pharmaceutical applications subject to the applicable laws and regulations in each country (*).

Thermoplastics

Primol 382 is recommended as a food packaging-grade plasticizer in Polystyrene. It combines outstandingly low volatility and excellent compatibility with Polystyrene for optimal performance in General Purpose and High Impact PS grades.

Primol 382 is recommended for use as an external lubricant for non-plasticized PVC.

Primol 382 is an inert and protective catalyst carrier for polypropylene processes. It can also serve as a pigment powder dispersant in master batch compounding.

Elastomers and Adhesives

Primol 382 is used for producing food-contact or medical rubber articles such as EPDM or butyl rubber. It is particularly well suited for the extension of Thermoplastic Elastomers (TPE), such as SBS, SEBS or SEPS.

Primol 382 is also recommended for Hot-Melt Adhesives formulations used in sanitary products.

Cosmetics and Pharmaceuticals

Primol 382 has many well-established applications in the pharmaceutical industry, like laxative jellies and ointments, and is also recommended as a component for many cosmetic products, such as creams and body lotions.

Further detailed information is available in our bulletin White oils for Cosmetics.

(*) User must check compliance with applicable regulations. As an example, at the date of this publication, Primol 382 can be used as a food additive in USA subject to applicable FDA regulations, while it cannot be used as a direct food additive in European Union Member States

Properties and Specifications

Primol 382 meets the requirements of the following specifications:

- USA FDA, 21 CFR 172.878 and 21 CFR 178.3620(a), White Mineral Oil
- US Pharmacopoeia, most recent edition, Mineral Oil
- National Sanitation Foundation (NSF), registration number 132484
- European Pharmacopoeia, most recent edition, Liquid Paraffin
- European Directive for plastic materials into contact with food, 2002/72/EC, White Mineral Oil
- The Japan's Specifications and Standards for Food additives, Liquid Paraffin

CAS number: 8042-47-5

EINECS number: 232-455-8

INCI name (Europe): Paraffinum Liquidum

CTFA Dictionary name (USA): Mineral Oil

Property	Test Method	Typical	Specification	
			Min.	Max.
Appearance	Visual	-	Clear and Bright	Clear and Bright
Odor	Olfactory	-	Absent	Absent
Color, Saybolt	ASTM D 156	-	+ 30	-
Kinematic Viscosity @ 40°C, mm ² /s	ASTM D 445	-	67.0	78.0
Kinematic Viscosity @ 100°C, mm ² /s	ASTM D 445	-	8.6	-
Density @ 15 oC, kg/m ³	ASTM D 4052	-	863	873
Pour Point, oC	ASTM D 97	-	-	- 9
Flash Point, oC	ASTM D 92	-	240	-
Refractive Index, nD ₂₀	ASTM D 1218	-	1.473	1.478
Average Molecular Weight	ASTM D 2502	-	485	-
Hydrocarbons with 25 carbons and less, wt %	ASTM D 2887	-	-	3
Volatility @10 mm Hg, temp (°C) at which 2.5 % off	ASTM D 1160	284	-	-
Volatility @10 mm Hg, temp (°C) at which 5 % off	ASTM D 1160	291	288	-
Volatility @10 mm Hg, temp (°C) at which 10 % off	ASTM D 1160	295	292	-
Carbon Type, % and Paraffinic / Naphthenic / Aromatic	ASTM D 2140	67 / 33 / 0	-	-

Typical values may vary within modest ranges and specifications may be subject to change.

Health and Safety

Detailed health and safety information for this product is provided in the Material Safety Data Sheet (MSDS), available upon request through your local sales representative or from www.ExxonMobil.com

Storage and Handling

Recommended storage and handling procedures for ExxonMobil white oil products are summarised in a separate bulletin available upon request through your local sales representative or from www.ExxonMobil.com

Further Information

ExxonMobil supplies a range of white oils, process oils, waxes, bitumen and a full range of other lubricants, fuels and chemical products worldwide. Please contact your local ExxonMobil representative, or contact us at www.ExxonMobil.com, for more information on other products.

The ExxonMobil logotype (and any other trademarks) are trademarks of Exxon Mobil Corporation or one of its subsidiaries.

ESSO Société Anonyme Française
Tour Manhattan
La Défense 2

5/6 Place de l'Iris
92400 Courbevoie
FRANCE

<http://www.exxonmobil.com>

Compte tenu de la continuité dans la recherche et le développement des produits, les informations de cette fiche descriptive sont données à titre indicatif et n'engagent en aucun cas le fabricant. Certains produits peuvent ne pas être disponibles localement.

Copyright © 2001-2014 Exxon Mobil Corporation. All rights reserved.