

Shell Helix Ultra VX 5W-30

Ultimate protection for performance motoring



Shell Helix Ultra VX is a premium-grade, fully synthetic engine oil scientifically formulated that gives you maximum engine clean up properties with special cleansing agents that actively and continuously lock away harmful dirt and deposits

Shell Helix Ultra VX is a unique, fully synthetic lubricant giving ultimate engine protection for performance motoring, is approved by leading car manufacturers such as VW and other car brands equipped with particulate filters.

With Shell Helix Ultra VX you know you are doing the right thing for your car

Applications

- **Modern VW, Porsche and other Diesel passenger cars equipped with Diesel particulate filters, requiring an ACEA C3 oil in the owner's manual.**

Even in cold conditions rapid oil flow assures any easy start and contributes to engine protection.

Performance Features and Benefits

- **Fuel economy**
Exceeds fuel economy requirements of VW cars.
- **Protection Against Wear**
Enriched with long life additives and protective agents to provide a prolonged protection against sludge and to ensure maximum engine protection against costly engine wear, even in the toughest driving conditions and harshest climates.
- **Environmental Protection**
Specially formulated to reduce CO₂ (greenhouse gas) exhaust emissions. The use of selected base oils reduces oil consumption.
An extremely low chlorine content reduces the environmental impact of product disposal.
- **Easy start-up**

Specification and Approvals

Helix Ultra VX 5W-30 exceeds the following industry standards:

ACEA:	C3 ; A3/B4
VW	504/507
Porsche	C30

Advice

Advice on applications not covered in this leaflet may be obtained from your Shell Representative.

Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet that can be obtained from your Shell representative.

Protect the environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Physical Characteristics

Helix Ultra VX			5W-30
SAE Viscosity grade			5W-30
Kinematic Viscosity		ASTM D 445	
	at 40°C	mm ² /s	67.1
	at 100°C	mm ² /s	12.0
Viscosity Index		ISO 2909	178
Density at 15°C		kg/m ³ ASTM D 4052	847
Flash Point COC		°C ISO 2592	230
Pour Point		°C ISO 3016	- 39

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.