



RUST VETO 342

Data Sheet

RUST PREVENTIVE SOLVENT BASE PRODUCT WITH WAXY FILM

RUST VETO 342 is a rust preventive especially developed for use in critical situations and it is particularly suitable for long term indoor protection during the transport by sea, protection of large size pieces, outdoor storage, etc.

APPLICATION

RUST VETO 342 can be applied by spray, dip or brush.

REMOVAL

RUST VETO 342 can be removed by washing with cold solvent.

CHEMICAL-PHYSICAL CHARACTERISTICS

Appearance	cloudy liquid
Colour	light brown
Flash point	≤ 38°C [TOC]
Specific Gravity at 20°C†	0.83-0.84
Film thickness	30 μ
Dry to set time	2 hours
Coverage [approx]	60 m ² /kg
Protection time indoor	2 years
outdoor	10 months
Salt Spray Humidity Cabinet	< 120 hours

HEALTH & SAFETY

No toxic or carcinogenic, teratogenic or mutagenic known materials are contained in RUST VETO 342 such as nitrosamines, phenols, polychlorinated diphenyl, heavy metals, polinuclear hydrocarbons.

STORAGE

FLAMMABLE PRODUCT: STORE IN SUITABLE ROOMS

RUST VETO 342 maintains its chemical-physical and technical characteristics if stored in a sheltered place at temperatures ranging -5°C÷30°C for a maximum period of twelve months.

WASTE TREATMENT

RUST VETO 342 cannot be directly discharged. Follow national or local instructions.

C-00 X 106490 APPROVAL: D.Petta