

## Castrol Rustilo DWX 32

Dewatering corrosion preventive

### Description

Castrol Rustilo™ DWX 32 is a powerful solvent deposited corrosion preventive with good dewatering properties. The solvent, after evaporation, leaves a firm greasy protective film.

### Application

Rustilo DWX 32 is a medium to long term protective for use in severe conditions where a high degree of protection is required. It is ideal for protection of machine tools and components prior to storage or transportation. The product also shows good water displacing properties.

Although Rustilo DWX 32 can be applied by brushing or spraying, its dewatering action is most effective if the articles to be protected can be immersed in a dip tank.

### Advantages

- Forms an even and robust film.
- Stable film characteristics reduce run-off loss and thus increase process reliability.
- Fingerprint suppressant.
- Good water displacing and penetrating properties.
- High stability against acidic and alkaline contaminations.
- Long bath-lifetimes possible.
- Economical in application.

### Typical Characteristics

	Unit	Test Method	Value
Appearance	-	Visual	Dark brown fluid
Density @ 15 °C	kg/m <sup>3</sup>	ASTM D 4052	830
Flash Point	°C	DIN 51 755	> 38
Film Type	-	-	Firm, greasy
Total Film Forming Content	%	-	30
Film Thickness	µm	-	4
Consumption	kg/100 m <sup>2</sup>	-	1.2 - 1.6
Corrosion Protection	Month	Indoor Storage	18
	Month	Outdoor Storage	9
Drying time @ 20 °C	min	-	90

## Additional Information

- The claims on film thickness and consumption are average values. These are valid for smooth surfaces with good drain-off characteristics and simple geometries without holes or recesses.
- Average drying time is the time until the majority of the solvent is evaporated at ambient temperature and a relative humidity of 60 – 70%. The full corrosion protection will just be provided when the solvent is completely evaporated.
- "Indoor storage" describes the storage of ferrous components in closed store-rooms having a relative humidity of 60%. Increased protection times could be achieved when treating finished surfaces or store the parts in a sealed pack.
- "Outdoor storage" describes open storage, which assumes primary protection from the elements by tarpaulin or other form of cover.
- Influence of temperature may cause some cloudiness, which is reversible and doesn't have an impact on product quality.
- If required protective films of Rustilo DWX 32 can easily be removed by using a petroleum solvent or alkaline process cleaner, all available from Castrol.

Castrol, Rustilo DWX, and the Castrol logo are trademarks of Castrol Limited, used under licence

INTERNATIONAL All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol Ltd products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product.

Castrol Limited, Pipers Way, Swindon, Wiltshire SN3 1RE, UK  
[www.castrol.com/industrial](http://www.castrol.com/industrial)