



# CINDOLUBE HPE

## Data Sheet

### VANISHING FLUID WITH HIGH LUBRICANT CHARACTERISTICS

CINDOLUBE HPE is an ecological, vanishing fluid which contains polar and antiwear additives of new generation.

CINDOLUBE HPE has shown excellent performances in aluminium blanking operations and it is also suitable for mild steel sheets working and:

- Shearing
- Forming
- Drawing

The use of the product is especially suggested when you want to avoid workpieces cleaning.

### CHEMICAL - PHYSICAL CHARACTERISTICS

Colour	Clear liquid
Specific gravity at 15.5°C	0.78 – 0.81
Flash point [Closed]	60°C
Viscosity at 40°C	2.5 – 3.5 cSt

### APPLICATION

CINDOLUBE HPE is applied as follows:

- Roll
- Felt
- Drop by drop or low pressure spray

### STORAGE

CINDOLUBE HPE maintains its chemical-physical and technical characteristics if stored in a sheltered place at temperatures of 40°C maximum for period of twelve months.

### HEALTH & SAFETY

No toxic or carcinogenic, teratogenic or mutagenic known materials are contained in CINDOLUBE HPE such as nitrosamines, phenols, polychlorinated diphenyl, heavy metals, polynuclear hydrocarbons.

Handle CINDOLUBE HPE with normal care given to flammable industrial products.

### WASTE TREATMENT

CINDOLUBE HPE cannot be directly discharged. Follow local or national instructions.

G/01-x0151-APPROVAL: G.PELLERANO