

**HOUGHTON ITALIA S.p.A.**



**Direzione - Sezione Amministrativa**  
**Ufficio Vendite-Acquisti**  
16162 Genova - Bolzaneto  
Via Pastorino 38  
Tel. +39-010-726.41.1  
Telefax +39-010- 745.00.55

**Produzione - Sezione Marketing**  
**Tecnica - Ricerca**  
16161 Genova - Teglia  
Via F.lli Bronzetti 22  
Tel. +39-010-741.02.1  
Telefax +39-010- 740.73.75

# CINDOLUBE K10

## LUBRICATING OIL VANISHING TYPE FOR MAGNETIC STAMPING

CINDOLUBE K10 is a lubricant product VANISHING type for magnetic stamping. This product contains an odourless solvent that evaporates quickly and do not leaves any kind of residuals, it means that it is not necessary the cleaning of small parts after blanking.

### APPLICATION:

Blanking of magnetic stamping at high speed.

### BENEFITS:

- Excellent rust prevention
- Absence of odour
- Cleaning of matrix
- Long life of matrix
- Evaporation "total control"

### CHARACTERISTICS:

Appearance: liquid limpid

Colour: pale yellow

Volumic weight at 15,5°C: 0,77

Viscosity at 40°C: 1,7 mm<sup>2</sup> /sec (cSt)

Flash point (closed cup): 48°C

### HEALTH & SAFETY

No toxic or carcinogenic, teratogenic or mutagenic known materials are contained in CINDOLUBE K10 such as nitrosamines, phenols, polychlorinated diphenyl, heavy metals, polinuclear hydrocarbons.

For the handling of CINDOLUBE K10 pay normal care usually given to industrial products.

### STORAGE

CINDOLUBE K10 maintains its chemical-physical and technical characteristics if stored in a sheltered place at temperatures ranging -5°C-40°C for a maximum period of 12 months.

### WASTE TREATMENT

CINDOLUBE K10 cannot be directly discharged. Follow

APPROVAZIONE G.Pellerano