


MOLYDUVAL

Contactin CU



Special Grease for Electric Contacts

A special lubrication and protection grease for electric contacts. Because of contained metall powders the electric conduction will be increased and dynamic motion goes easier. Prevents spark erosion and burning residues at electric contacts.



Properties

- * oxidation resistant
- * water refusing
- * good water resistance
- * extended drain intervals reduces oil disposal, thus increasing cost effectiveness
- * low noise
- * compatible with many seals and plastics
- * reduces contact wear
- * reduces contact resistance
- * freely of acids

Applications

- * for mechanic instruments
- * for electrical contacts
- * for electrical contacts, also for preservation

Technical Datas

Color		copper
Penetration	0,1 mm	200-250
Density 15°C	kg/m ³	990
Temperature Range	°C	-30 -> +180
Dropping Point	°C	180
Particle Size Ø	µm	45

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.

For more technical information contact us !

The technical data in this information sheet represents our present knowledge and is based on our general experience. It is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary tests with the selected product. It does also not form part of any sales contract as guaranteed properties of the delivered...

The information may be affected by changes occurring subsequent to the date of printing in the blend formulation or methods of application. Updating : 13.06.2008