

MOLYDUVAL

Corona 22



Textile Machinery Oil

Clear mineral oil intended for use in spinning frame bolsters, sewing machines, knitting machines and as a textile ring lubricant in spinning, twisting and draw-twisting operations. It is also effective in the lubrication of air tools and other high speed machine tools. Available also in other viscosities.

Properties

- * compatible with mineral oil
- * high pressure ability
- * good lubrication performance
- * reduces friction between the yarn and the guide
- * good moistening
- * good viscosity temperature correlation
- * water mixable
- * clear and transparent
- * water washable
- * compatible with many seals and plastics

Applications

- * for textile machinery
- * for use in spinning frame bolsters, sewing machines
- * for machines used to make polyester, nylon and PTFE/cotton blend fabrics
- * for spinning, twisting, and draw twisting operations
- * for textile machines, f.e. circular knitting machines

Technical Datas

Color		clear
Base Fluid		Mineral
Viscosity Class	ISO-VG	22
Viscosity Index	--	97
Pour Point	°C	-12
Density 15°C	kg/m ³	870
Viscosity 40°C	mm ² /s	22
Flash Point	°C	175

For more technical information contact us !

The technical data in this information sheet represents our present knowledge and is based on our general experience. It is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary tests with the selected product. It does also not form part of any sales contract as guaranteed properties of the delivered material.