





# Quick GN

Page 1 of 2



1400°C

-50°C

## Synthetic High Temperature Nuclear Grade Lubrication Paste

MOLYDUVAL Quick GN is a lubrication paste for extreme temperatures and high pressures. It is also used as a running-in, assembly and multipurpose paste in special cases.

MOLYDUVAL Quick GN reduces friction and wear, assembly and disassembly will go easier. The solid lubricant graphite protects against wear, running-in defects and guarantees good antifrictional properties.

MOLYDUVAL Quick GN is free of metals, copper, sulphur, so that screw materials will not be affected by it. Quick GN even contains no hazardous components.

### PROPERTIES

- water- and corrosion resistant
- exceptional good lubricating-effect
- prevent seizing and rusting
- reduces the friction coefficient to a minimum
- decreasing friction coefficient with increasing pressure
- antiwear characteristics
- less residues because of special synthetic oil base

### APPLICATIONS

- for assembly of wave-nave-combinations (wheels, antifriction bearing, discs, bolts, flangers and so on) if the friction coefficient should be reduced at high pressures. Seizing and stick-slip will be avoided
- for screws and lubrication points at turbines, gears, ventiles, chains, which are presented f e in petrochemical or power plants

### HOW TO USE

Apply MOLYDUVAL Quick GN thin and even with brush or rag on the cleaned surfaces. Avoid surpluses.

