

Mobil Mist Lube Series

Gear Oils

Product Description

Mobil Mist Lube Series are extra high performance oils designed for the oil-fog or mist-lubrication of machine components such as slideways, bearings, gears, chains etc. They are formulated from high quality, solvent refined base stocks and a unique additive system designed for optimum reclassifying properties. They have a high resistance to oxidation and good extreme pressure and anti-wear properties. The products have enhanced surface wetting capabilities and they reclassify (or agglomerate) readily from a mist to a liquid when the mist is subjected to extreme turbulence or is impinged onto a surface at high velocity. This allows a lubricating film to form on bearings and gears and prevents stray mist from escaping through narrow apertures into the atmosphere.

The available viscosity grades in the Mobil Mist Lube Series are ISO VG 32 and 100.

Features and Benefits

The Mobil Mist Lube Series of products is an important member of the Mobil brand of lubricants and enjoy recognition among equipment operators for their superb performance capabilities in misting applications. Mobil Mist Series oils were developed specifically for mist applications and have undergone an arduous protocol of testing, including misting performance, in their development. Mobil Mist Lube Series offer the following features and potential benefits:

Features	Advantages and Potential Benefits
Superior mist forming and reclassifying properties	Ensures even distribution of lubricant on machine parts with control of stray mist for reliable lubrication and problem-free operation, reduced leakage and lower oil consumption
Excellent EP and anti-wear performance	Prevents machine element wear with resulting savings in maintenance and parts replacement
High quality base oil and additive components	Avoids reclassifier plugging problems which can result in catastrophic bearing and gear failure, with accompanying downtime and replacement costs
Excellent resistance to oxidation	Long product life, reduced product and maintenance costs
Very good rust protection including sea water	Excellent equipment protection

Applications

Mobil Mist Lube Series oils are designed for use in all oil mist lubrication systems. Such systems work by dispersing very small droplets of oil in smoothly flowing air, distributing the oil mist to the points of application and mechanically condensing the mist, causing the oil to impinge on and wet the surfaces to be lubricated. The higher viscosity Mobil Mist Lube grades may require thermal misting devices to form proper dispersions when ambient temperatures are moderate or low. Mobil Mist Lube 24 is suitable for oil / air delivery systems such as airline oilers. Specific applications include:



- Industrial gearing such as cooling tower gearboxes
- Slow-speed, heavily-loaded bearings (higher viscosity grades)
- High-speed bearings (lower viscosity grades)
- Machine tools, ways and screws
- Process pumps, electric motors and blowers
- Steam turbines and electric motors

Typical Properties

Mobil Mist Lube Series	24	27
Viscosity, ASTM D 445		
cSt @ 40°C	32	100
cSt @ 100°C	5.5	11.2
Viscosity Index, ASTM D 2270	110	95
Pour Point, °C, ASTM D 97	-12	-12
Flash Point, °C, ASTM D 92	210	234
Density @15.6 °C, ASTM D 4052, kg/l	0.88	0.89
FZG Scuffing, DIN 51534, A/8.3/90, Fail Stage	12+	12+
4-Ball EP test, ASTM D 2783, Weld Load, kg	160	250
Load Wear Index, kgf	25	48
4-Ball Wear Test, ASTM D 4172 mod, (20kg/54°C/1800rpm/1 hr), Scar, mm	0.5	0.3
Timken OK Load, ASTM D 2782, lb	50	65
Rust protection, ASTM D 665, Sea Water	Pass	Pass

Precautions

MOBIL MIST LUVE is manufactured from high quality petroleum base stocks, carefully blended with selected additives. As with all petroleum products, good personal hygiene and careful handling should always be practiced. Avoid prolonged contact to skin, splashing into the eyes, ingestion or vapour inhalation. Please refer to our Imperial Oil Material Safety Data Sheet for further information.

Note: This product is not controlled under Canadian WHMIS legislation.

The Mobil logotype and the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.