



Search...

Can't find what you're looking for?
Search for it here.

- [HOME](#) [PRODUCTS ▼](#) [INDUSTRIES ▼](#) [BROCHURES ▼](#) [OUR COMPANIES](#)
[CONTACT](#)

HUSKEY™ DYNA-MITE RED GREASE

Description

HUSKEY DYNA-MITE RED GREASE is a unique high-temperature, extreme pressure, non-melting premium quality grease designed for very heavy-duty service in adverse environments. It is a blend of high quality petroleum oil and special synthetic polymers which work together to form an extremely water-resistant, tough lubricating film that prevents water washout and metal-to-metal contact even under extreme pressure or shock loading. **HUSKEY DYNA-MITE RED GREASE** is formulated with the optimum amounts of additives to provide maximum protection against rust, corrosion and oxidation. **HUSKEY DYNA-MITE RED GREASE** contains no fillers or clay thickeners. The distinctive red color makes it easy to identify during and after lubrication.

Advantages

- WITHSTANDS EXTREME PRESSURES
- WIDE TEMPERATURE RANGE (10°F TO 525°F)
- EXTREMELY RESISTANT TO WATER WASHOUT
- EXCELLENT METAL ADHERENCE
- WILL NOT MELT OR RUN OUT
- PREVENTS RUST AND CORROSION
- REDUCES WEAR

Usage

HUSKEY DYNA-MITE RED GREASE with its unique qualities can be used in a wide variety of applications, thus reducing the number of lubricants you must keep on hand. Some such applications include ball and roller bearings, bushings, slides, valve operators and bearings, gears, screw drives, couplings, cranes and general lubrication, especially where loads may be quite heavy and speeds slow.

Package Availability

- Convenient Disposable Gun Loader 14 oz. Cartridges
- 5 gal. Pail
- 15 gal. Keg
- 55 gal. Drum

Typical Specifications

Product: DYNA-MITE RED GREASE


Color: Red

Thickener: Synthetic

Base Oil: Semi-Synthetic

Texture: Buttery

Test	ASTM Test Method	Typical Results
N.L.G.L. Grade		2
Worked Penetration		
<i>60 Strokes</i>	D-217	275
<i>10,000 Strokes</i>	D-217	290
Base Oils Viscosity,		
<i>SUS @ 100°F</i>	D-445	3650
<i>SUS @ 210°F</i>	D-445	200
<i>cSt @ 40°C.</i>	D-445	677
<i>cSt @ 100°C</i>	D-445	40
Pour Point °F	D-97	10
Flash Point	D-92	525
Dropping Point, °F	D-566	NONE
Corrosion Preventative Test	D-1743	PASS
Timken OK Load, lbs.	D-2509	60

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

[Return](#)

Copyright 2016 by HUSK-ITT Corporation. Login