



Search...

Can't find what you're looking for?  
Search for it here.

- [HOME](#)  
 [PRODUCTS ▼](#)  
 [INDUSTRIES ▼](#)  
 [BROCHURES ▼](#)  
 [OUR COMPANIES](#)  
[CONTACT](#)

## HUSKEY™ 2000

### LUBRICATING PASTE AND ANTI-SEIZE COMPOUND FOR HIGH TEMPERATURE

#### Description

**HUSKEY 2000** is a heavy-duty industrial anti-seize and lubricating paste containing very finely divided metallic particles in a special no-melt semi-synthetic carrier. **HUSKEY 2000** leaves a protective film that seals and protects metal parts even under the most extreme conditions of heat, pressure, steam and saltwater exposure.

#### Advantages

**HUSKEY 2000** is not just another anti-seize/thread lubricant. Unlike conventional products on the market, the maximum blend of metallic solids has been homogenized into a specially designed semi-synthetic lubricating grease which does not contain clay or soap base thickeners. This helps to provide a superior product that will not melt and run out after application. It also helps to reduce friction of metal surfaces and allows easy movement of threaded connections during assembly and dis-assembly which makes for tighter make-ups and leak free joints. Other advantages include:

- PROTECTS TO +2000°F.
- REDUCES TORQUE
- PREVENTS CARBON FUSION
- PREVENTS RUST & CORROSION
- EXCELLENT LUBRICITY
- PREVENTS GALLING & SEIZING
- STEAM & WATER PROOF
- CHEMICAL RESISTANT
- EXTREME PRESSURE LUBRICANT
- NON-MELTING

#### Usage

**HUSKEY 2000** was designed as a preventative maintenance tool providing complete parts protection on threaded fittings and all metal surfaces subjected to harsh environments or high temperatures to +2000°F. **HUSKEY 2000** was formulated to fit a wide variety of marine, metal working, automotive, oilfield, construction and farm equipment applications. A few such examples include.

- THREADED FITTING
- RIG DRIVES
- SPROCKETS & CHAINS
- CASTING EQUIPMENT
- SPLINES
- LOW SPEED WORM GEARS
- MANIFOLD STUDS & BOLTS
- WINCHES
- BRAKE CAMS & PINS
- CONVEYORS
- VALVE SHAFTS
- SENSORS

#### Package Availability

- 3 gram Lube-Paks® (packed 1000 per case)
- ½ Pint Brush Top Jar (packed 12 to a case)
- 1 Pint Brush Top Jar (packed 12 to a case)
- Convenient 1 gal. Jugs (4/case)

- 5 gal. Pail
- 15 gal. Keg
- 55 gal. Drum

## Typical Specifications

**Product:** 2000 ANTI-SEIZE

**Base Oil:** Semi-Synthetic

**Thickener:** Synthetic

**Color:** Copper Gray

**Texture:** Buttery

**U.S.D.A. Rating:** H-2

TEST	ASTM TEST	RESULTS
N.L.G.I. Grade		1
Penetration		
<i>Unworked</i>	D-217	290
<i>Worked, 60 strokes</i>	D-217	320
Base Oil Viscosity,		
<i>SUS @ 100°F</i>	D-445	4292
<i>SUS @ 210°F</i>	D-445	223
<i>cSt @ 40°C</i>	D-445	796
<i>cSt @ 100°C</i>	D-445	46
Pour Point, °F	D-97	14
Flash Point, °F	D-92	450
Dropping Point, °C (°F)	D-566	None
Copper strip corrosion (24hrs. @ 210°F)	D-4048	1A
Salt Spray Test 5% Salt, 24hrs. @ 95°F	B-117	No Corrosion
Coefficient Friction (LFW-4)		
<i>Static</i>		0.121
<i>Dynamic</i>		0.079
Four Ball Wear Scar, mm (40Kg, 1 hr @ 1200 rpm)	D-2266	0.92

[SAFETY DATA SHEET](#)

[Call for a Quote](#)

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied, whether for merchant ability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

[Return](#)

Copyright 2016 by HUSK-ITT Corporation. [Login](#)