



Search...

Can't find what you're looking for?  
Search for it here.

HOME   PRODUCTS ▼   INDUSTRIES ▼   BROCHURES ▼   OUR COMPANIES  
CONTACT

## HUSKEY™ TF-1000 MULTI-PURPOSE PTFE GREASE

### Description

**HUSKEY TF-1000 GREASE** is a versatile, multi-purpose grease containing powdered PTFE. It is blended from the highest quality selected oils and synthetic bases available. It is compounded by special processes and techniques to guarantee thorough dispersion and homogenization of the PTFE lubricating solids. A highly water resistant high temperature adhesive lubricant with the unique characteristics of PTFE. Rust and oxidation inhibiting characteristics are maximized to afford complete rust protection and long life of the lubricant.

### Advantages

- Plating Action is established between the metal-surfaces by the micron size self-lubricating PTFE that develops a smoother surface.
- Working life of both old and new parts is increased due to the PTFE filling in any metal imperfections.
- Friction is lowered, reducing contact and temperature, resulting in increased working life of the grease.
- Cost reduction is accomplished by increased parts life, less down-time and extended lubricating cycles.
- Light color base for use where positive evidence of lubrication depends on visual check or where cleanliness is preferred.

### Usage

**HUSKEY TF-1000** was especially designed to provide superior high-temperature performance. It was also engineered to afford excellent results in a wide variety of automotive, marine, household, agricultural, and industrial applications, such as: wheel bearings, ball joints, conveyors, universal joints, pilot bearings, electric motors and general plant lubrication; including all guide rails and sliding applications.

### Package Availability

- Convenient Disposable Gun Loader 14 oz. Cartridges
- 1 gal. Pail
- 5 gal. Pail
- 15 gal. Keg
- 55 gal. Drum

### Typical Specifications

**Product:** TF-1000

**Color:** Cream


**Base Oil:** Semi-Synthetic

**Thickener:** Synthetic

**Texture:** Buttery

**Base Solid Lubricant:** PTFE

TEST	ASTM TEST	RESULTS
N.L.G.I. Grade		2
Worked Penetration, 60 strokes	D-217	265 - 295
Base Oil Viscosity,		
<i>SUS @ 100°F</i>	D-445	781
<i>SUS @ 210°F</i>	D-445	76
<i>cSt @ 40°C</i>	D-445	135
<i>cSt @ 100°C</i>	D-445	14
Pour Point, °F	D-97	5
Flash Point, °F	D-92	525
Dropping Point, °F	D-566	NONE
Corrosion Preventative Test	D-1743	PASS
Timken OK Load, lbs	D-2509	45

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

[Return](#)

Copyright 2016 by HUSK-ITT Corporation. Login