



Search...

Can't find what you're looking for?
Search for it here.

- [HOME](#)
 [PRODUCTS ▼](#)
 [INDUSTRIES ▼](#)
 [BROCHURES ▼](#)
 [OUR COMPANIES](#)
[CONTACT](#)

HUSKEY™ LUBE-O-SEAL

Description

HUSKEY LUBE-O-SEAL is a versatile, pure synthetic, completely waterproof grease containing PTFE. It is formulated to seal out water and lubricate under the most adverse conditions. **HUSKEY LUBE-O-SEAL** with its highly adhesive qualities and high load-carrying characteristics forms a tough durable film of lubrication that prevents metal-to-metal contact even under severe shock loads. **HUSKEY LUBE-O-SEAL** is also NSF/U.S.D.A. H-1 *Registered and KOSHER approved, which gives it full acceptability for use in ALL areas where incidental food or potable water contact may occur.

Advantages

- NSF/U.S.D.A. H-1 *Registered
- WATERPROOF
- NON-MELTING
- CONTAINS PTFE
- KOSHER APPROVED
- BIODEGRADABLE
- CHEMICALLY RESISTANT
- NON-STAINING
- WIDE TEMPERATURE RANGE
- REDUCES WEAR
- PREVENTS RUST & CORROSION
- HIGH DIELECTRIC STRENGTH

*NSF H-1 Registration No. 059322

Usage

HUSKEY LUBE-O-SEAL with its waterproof and chemical resistant capabilities is an excellent lubricant on all sliding surfaces, gears and slow to moderate speed bearings (about 1000 RPM maximum) operating in WET or DRY conditions from 20°F to 350°F. Due to its pure synthetic base, coupled with the addition of sub-micron size PTFE, **HUSKEY LUBE-O-SEAL** is an excellent choice for applications in many Industries, which requires a clean, tenacious, anti-wear grease. Because of its NSF/U.S.D.A. H-1 *Registration, **HUSKEY LUBE-O-SEAL** is outstanding for use in food processing plants, where equipment wash down is an everyday requirement and water Industries, where contamination with conventional petroleum lubricants is a primary environmental concern.

HUSKEY LUBE-O-SEAL is compatible with most rubbers and plastics and is a superior lubricant for "O" rings. Some of its diversified uses include:

- OPEN GEARS
- FOOD EQUIPMENT
- SLIDES AND WAYS
- STERILIZER CHAINS
- GASKETS AND "O" RINGS
- CONVEYORS
- VALVES
- BUSHINGS
- TRUNNIONS
- POOL EQUIPMENT

CAUTION: BEFORE PRODUCT IS UTILIZED IN AUTOMATIC LUBRICATION EQUIPMENT, PLEASE CONSULT THE HUSK-ITT CORPORATION FOR RECOMMENDATION.

Package Availability



- 3 oz. Tubes

- Convenient Disposable Gun Loader 14 oz. Cartridges
- 5 gal. Pail
- 15 gal. Keg
- 55 gal. Drum

Typical Specifications

Product: LUBE-O-SEAL :
Solid Lubricant: PTFE **NSF/U.S.D.A. Rating:** H-1
Base Oil: Synthetic **Thickener:** Synthetic
Color: Translucent White **Texture:** Smooth & Tenacious

Test	ASTM Test Method	Results
N.L.G.L. Grade		2
Worked Penetration		
<i>60 Strokes</i>	D-217	280
<i>10,000 Strokes</i>	D-217	290
Base Oils Viscosity,		
<i>cSt @ 100°C</i>	D-445	200
<i>cSt @ 40°C</i>	D-445	7800
Pour Point, °F	D-97	20
Flash Point, °F	D-92	350
Dropping Point °F	D-566	None
Evaporation Loss, % (10 hours @ 210°F)	D-972	1.0
Corrosion Preventative Test	D-1743	PASS
Water Washout, % Loss	D-1264	0.01
Timken OK Load, lbs.	D-2509	40
4-Ball Wear Scar, mm (40 Kg, 75 ° C, 1 hr. @ 1200 rpm)	D-2266	0.57
Dielectric Strength, KV	D-877	30



SAFETY DATA SHEET
NSF REGISTRATION
KOSHER LETTER

Call for a Quote

The name of this product or group of products is for product identification only. HUSK-ITT Corporation. makes no warranties, representations or conditions of any kind expressed or implied, whether for merchant ability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT Corporation sales personnel are not authorized to amend this warranty limitation.

[Return](#)

Copyright 2016 by HUSK-ITT Corporation. Login