

# \* PRODUCT INFORMATION \*

## **HUSKEY™ WIRELINE DRESSING**

### **DESCRIPTION**

**HUSKEY WIRELINE DRESSING** is a heavy duty, tenacious, semi-synthetic penetrating grease fortified with sub-micron size particles of Molybdenum Disulfide (Moly) and Graphite. This high performance liquid grease goes on as a liquid to penetrate to the core of the wire rope. After it penetrates and coats the metal surfaces, the carrier solvent evaporates, leaving behind a tough, durable grease film that protects under the most adverse conditions.

**HUSKEY WIRELINE DRESSING** completely protects the core of wire rope and all metal surfaces from moisture, chemicals, salt water and other corrosive conditions. The balanced blend of lubricating solids and extreme pressure additives provides excellent lubricity and low coefficient of friction to minimize excessive shock loads and reduce wear.

### **USAGE**

**HUSKEY WIRELINE DRESSING** is designed primarily for wire rope and cable protection and lubrication. Excellent results have been found on application to open gears, roller chains, sliding surfaces, gibs, guides and ways, etc., where a liquid application is required or preferred.

**HUSKEY WIRELINE DRESSING** is easily applied by spraying, brushing or dipping,

**HUSKEY WIRELINE DRESSING** penetrates deep into the core of wire lines carrying the oils and lubricating solids to provide maximum protection from wear due to twisting, bending, and stretching.

### **ADVANTAGES**

- Penetrates
- Withstands Extreme Pressures
- Wide Temperature Range (0°F to 450°F)
- Extremely resistant to Water Washout
- Excellent Metal Adherence
- Will Not Melt or Run Out
- Reduces Wear

### **PACKAGE AVAILABILITY**

5 gal. Pails, 15 gal. Kegs and 55 gal. Drums



## **HUSKEY Specialty Lubricants**

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

### **Western Region Office:**

1580 Industrial Avenue, Norco, California 92860  
(951) 340-4000 • Fax: (951) 340-4011  
(888) 4-HUSKEY • [www.huskey.com](http://www.huskey.com)

### **Eastern Region Office:**

8300 Corporate Park Drive, Macedonia, Ohio 44056  
(330) 425-2567 • Fax: (330) 425-9637  
(800) 238-LUBE

# \* PRODUCT INFORMATION \*

## TYPICAL PROPERTIES

<b>DESCRIPTION</b>	<b>HUSKEY</b> Product:	WIRELINE DRESSING
	Color:	Black
	Base Oil:	Semi-Synthetic
	Thickener:	Synthetic
	Appearance:	Black Fluid as received

<u>TEST</u>	<u>ASTM METHOD</u>	<u>RESULTS AFTER SOLVENT EVAPORATION</u>
N.L.G.I. Grade	----	2
Worked Penetration (without solvent carrier)	D-217	
60 Strokes		275
10,000 Strokes		290
Base Oil Viscosity,	D-445	
SUS @ 100°F		4100
SUS @ 210°F		280
Pour Point, °F	D-97	0
Flash Point, °F	D-92	450
Dropping Point, °F	D-566	NONE
Corrosion Preventative Test	D-665	PASS
Timken OK Load, lbs.	D-2509	60

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

4/08



## **HUSKEY Specialty Lubricants**

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

### **Western Region Office:**

1580 Industrial Avenue, Norco, California 92860  
(951) 340-4000 • Fax: (951) 340-4011  
(888) 4-HUSKEY • www.huskey.com

### **Eastern Region Office:**

8300 Corporate Park Drive, Macedonia, Ohio 44056  
(330) 425-2567 • Fax: (330) 425-9637  
(800) 238-LUBE