Search ...



Can't find what you're looking for? Search for it here.

HOME **PRODUCTS •** INDUSTRIES **T BROCHURES T OUR COMPANIES**

CONTACT

HUSKEYTM COOLUBE 65 GREASE

Description

HUSKEY COOLUBE 65 is a high performance, low temperature grease designed for high speeds and moderate loads. HUSKEY COOLUBE 65 is blended from the highest quality petroleum base stocks and selectively treated with rust, oxidation and anti-wear additives coupled with an extremely shear stable thickener system.

Advantages

- WIDE TEMPERATURE RANGE
- EXCELLENT FOR HIGH SPEEDS
- EXTREMELY RESISTANT TO WATER

- PREVENTS RUST AND CORROSION
- EXTREME PRESSURE RESISTANT
- REDUCES FRICTION AND WEAR

Meets the Requirements of Mil - PRF-10924 C&D and Ford WSB-M1C163-D

Usage

HUSKEY COOLUBE 65 was designed to provide excellent lubrication, wet or dry, over a wide temperature range (-65°F to 250°F.) in a large variety of industries, including textile, food processing, agriculture, automotive, etc. HUSKEY COOLUBE 65 meets the performance requirements of MIL-G-10924C and MIL-G-10924D. COOLUBE 65 is recommended for all bearing surfaces including fan bearings, spindles, freezer bearings, electric tools, slides, conveyors, etc.

Package Availability

- Convenient Disposable Gun Loader 14 oz. Cartridges
- 1 gal. Pail
- 5 gal. Pail
- 15 gal. Keg
- 55 gal. Drum

Typical Specifications

Product: COOLLUBE 65 Color: Amber Thickener: Calcium 12 Hydroxy Test **ASTM Test Method Typical Results** N.L.G.L.Grade Worked Penetration, 60 Strokes D-217 265-295

2

| 17.9.2018 | HUSKEY™ COOLUBE 65 GREASE | | |
|------------------------------------|---|--------|------|
| | Base Oils Viscosity, | | |
| | cSt @ 40°C | D-445 | 15.1 |
| | cSt @ 100°C | D-445 | 3.2 |
| | Pour Point °F | D-97 | -65 |
| | Flash Point | D-92 | 300 |
| | Dropping Point, °F | D-566 | 300 |
| | Oxidation Stability, (100 hrs. @ 210°F) psi D-942 Loss | | 5 |
| | Oil Separation, % Loss | D-1742 | 5 |
| | Rust Test | D-1743 | Pass |
| | Timken OK Load, Ibs. | D-2509 | 45 |
| SAFETY DATA SHEET Call for a Quote | | | |

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

<u>Return</u>

Copyright 2018 by HUSK-ITT Corporation. Login