

BECHEM High-Lub LIC 00-000

Part-No. 9003272

EP semi-fluid grease



Product description

BECHEM High-Lub LIC 00-000 is an EP fluid grease of NLGI class 00-000 designed for the lubrication of gears, rolling and plain bearings as well as for the application in centralized lubrication systems. BECHEM High-Lub LIC 00-000 provides reliable wear and corrosion protection even in case of water absorption.

Industries

- Automotive industry
- Cement industry
- Food industry
- Medical technology
- Mining
- Paper industry
- Pharmaceutical Industry
- Steel industry
- Textiles and apparel industry

Examples of application

- Small gearboxes with gears running at high peripheral speeds
- Lubrication points of commercial vehicles supplied by central lubrication systems

Properties

- Excellent wear protection based on the use of special additives
- Good water resistance
- Good adhesion on metallic surfaces
- Very good low temperature properties based on semi-synthetic base oil
- Excellent flow properties even at low ambient temperatures
- Very good corrosion protection

Characteristic data

Type	Unit	Value	Standard
Thickener		Lithium soap	
Base oil		Mineral oil, Synthetic oil	
NLGI-grade		00-000	
Color/Appearance		light yellow	
Kinematic viscosity of the base oil at 40 °C	mm ² /s	approx. 25	DIN 51562/ASTM D 7042
Kinematic viscosity of the base oil at 100 °C	mm ² /s	approx. 5	DIN 51562/ASTM D 7042
Worked penetration	1/10 mm	420 – 450	
Drop point	°C	≥ 150	
Working temperature range	°C	-30 – 80	
Working temperature range	°F	-22 – 176	
Denomination according to DIN 51502		GP 00-000 E-30	



BEICHEM High-Lub LIC 00-000

Part-No. 9003272

EP semi-fluid grease

Instructions for use

Please read the safety data sheet prior to use to learn about precautions and safety instructions. Always comply with the applicable safety provisions and the intended use. You can request a copy of the current safety data sheet using the contact form on our website www.bechem.de/kontakt or by e-mail to bechem@bechem.de.

Important notes

The information and technical data contained in this data sheet concerning the fields of application and processing for the product listed above are based on our knowledge and experience at the time of printing. Unless otherwise stated, this information is provided solely for reference and does not constitute a specification or warranty of quality in a particular instance. Many factors such as the relevant fields of application and the operating and working conditions are beyond the control of BEICHEM. **For this reason, we cannot guarantee the suitability of our products for a specific purpose or application on the part of the customer. The delivery of our products and our liability are subject exclusively to our general sales and delivery conditions. These are available online at www.bechem.de/agb.html.**

Information regarding material compatibility is based on extensive laboratory testing and literature references. Due to the large number of plastics used and their raw materials as well as the complex chemical and morphological polymer structure, the indications regarding compatibility are solely a reflection of general trends. In order to ensure that the product is used correctly for individual orders and particularly for serial production, we recommend that the supplier carries out its own trials and application tests in advance and confirms the compatibility of the product or carries out thorough laboratory tests.

Please refer to the current safety data sheet for information regarding: Hazardous material labelling, safety provisions, and regulations on storage and transport, and take any necessary precautions to protect property and persons.

Because BEICHEM products are subject to continuous development, CARL BEICHEM GMBH and its associated companies reserve the right to make changes to the technical data in this data sheet at any time.

Visible variations in the product color of each batch as well as changes in the color of delivered products are technically possible and even probable for some products (for instance, due to the influence of temperature on raw materials). These processes are normal and confirmed by BEICHEM raw material suppliers. They have no impact on the serviceability, service life, and quality of the products.

BEICHEM and BEICHEM Rhusblüte are registered trademarks of CARL BEICHEM GMBH. Logos, pictograms, and illustrations depicted in this data sheet are subject to copyright protection and may not be reproduced, modified, or disseminated without the express permission of BEICHEM.

For further information and more detailed product data, please contact us at: info@bechem.com or bechem@bechem.de.



Low temperatures



High speed



Good pumpability



Roller bearings



Plain bearings



Closed gears