

* PRODUCT INFORMATION *

HUSKEY™ 220-R SILICONE GREASE

DESCRIPTION

HUSKEY 220-R SILICONE GREASE represents the latest technology in lubrication. It is formulated from pure silicone base oils and selectively treated with rust, oxidation and anti-wear additives coupled with a shear stable thickener to provide maximum parts protection in a wide range of temperatures from -50°F to 570°F (-46°C to 299°C) **HUSKEY 220-R SILICONE GREASE** primary properties are that it is non-melting, has a high dielectric strength, low volatility and is insoluble in water, methanol, ethanol, dilute acids, caustics, glycol, glycerine, vegetable and mineral oils.

HUSKEY 220-R SILICONE GREASE is designed to be compatible with most plastics and rubbers, especially ethylene propylene terpolymer (EPDM, EPT) commonly used in Disc Brake Caliper systems.

HUSKEY 220-R SILICONE GREASE is also NSF/U.S.D.A. H-1 *Registered and KOSHER approved, which gives it full acceptability for use in ALL areas where incidental food or potable water contact may occur.

USAGE

HUSKEY 220-R SILICONE GREASE was originally designed as a problem solving, anti-corrosion lubricant for all moving caliper hardware, backing plates and seals of Disc Brake Caliper assemblies. However, due to its water, chemical and corrosion resistance capabilities it is an excellent choice in a wide variety of automotive, marine, agriculture, household and industrial applications. Some of its diversified uses include:

- DISC BRAKE CALIPERS
- BRAKE HARDWARE
- SPARK PLUG BOOTS
- BATTERY TERMINALS
- ELECTRICAL CONNECTIONS
- WEATHER STRIPPING
- GASKETS AND O'RINGS
- VALVES
- SLIDES AND WAYS
- POOL EQUIPMENT
- BUSHINGS
- MOTION CONTROLLERS

ADVANTAGES

- PREVENTS RUST & CORROSION
- CHEMICAL RESISTANT
- WIDE TEMPERATURE RANGE
- HIGH DIELECTRIC STRENGTH
- MEETS MIL-S-8660C SPECIFICATIONS
- NON MELTING
- EXTREMELY LOW VOLATILITY
- WATERPROOF, WILL NOT WASHOUT
- REDUCES WEAR
- *NSF H-1 Registered and KOSHER Approved

*NSF H-1 Registration No. 122832



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:
1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:
8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE

* PRODUCT INFORMATION *

TYPICAL PROPERTIES

<u>DESCRIPTION</u>	HUSKEY Product:	220-R Silicone Grease
	Color:	Translucent White
	Base Oil:	Polydimethylsilicone
	Thickener:	Synthetic
	Texture:	Tenacious
	Temperature Range:	-50°F to 570°F (-46°C to 299°C)

<u>TEST</u>	<u>TEST METHOD</u>	<u>RESULTS</u>
Penetration, Worked 60 strokes, mm	ASTM D-217	230-245
NLGI No.		3
Flash Point, °F (°C)	ASTM D-92	570 (299)
Drop Point, °F (°C)	ASTM D-566	None
Pour Point, °F (°C)	ASTM D-97	-50 (-46)
Base Oil Corrosion Test:	ASTM D-665	
Procedure A (distilled water)		Pass
Procedure B (synthetic sea water)		Pass
Oil Separation, % Loss	FTM 791.321	
24 hrs. @ 392°F (200°C)		0.0
Evaporation Loss, %	FTM 791.321	
24 hrs. @ 392°F (200°C)		.38
Elastomer Compatibility	ASTM D-4289	
EPDM Rubber, % Change		
(70 hrs. @ 250°F (121°C))		
Hardness		2.4
Swell		1.8
Corrosion Test,	ASTM D-1748	
100 hrs. @ 120°F (49°C)		Pass
Copper Strip Corrosion Test	ASTM D-4048	1a
Water Washout, % max.	ASTM D-1264	1.0
Dielectric Strength volts/mil, min.	ASTM D-149	800
Volume Resistivity, OHM-cm	ASTM D-257	1x10 ¹³
Dielectric Constant	ASTM D-150	2.8



PACKAGE AVAILABILITY

1-gal. Pails, 5-gal. Pails, 15-gal Kegs and 55-gal. Drums



The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation. 8/15



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
 (951) 340-4000 • Fax: (951) 340-4011
 (888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
 (330) 425-2567 • Fax: (330) 425-9637
 (800) 238-LUBE