

* PRODUCT INFORMATION *

HUSKEY™ 577

ALUMINUM ANTI-SEIZE COMPOUND

DESCRIPTION

HUSKEY 577 Anti-Seize is a general purpose, economical, industrial anti-seize and lubricating paste containing micro-sized aluminum particles and graphite in a special no-melt petroleum base grease. **HUSKEY 577 Anti-Seize** adheres well to metal surfaces and offers exceptional wear resistance. Therefore it can provide outstanding protection against galling, seizing and corrosion on metal surfaces even under the most extreme of heat, pressure, steam and water exposure.

USAGE

HUSKEY 577 was designed as a preventative maintenance tool providing complete parts protection on threaded fittings and all metal surfaces subjected to harsh environments or high temperatures to +1600°F. As it is free of copper, it can be safely used on stainless steel or other sensitive alloys. **HUSKEY 577** was formulated to fit a wide variety of metal working, automotive, oilfield, construction and farm equipment applications. A few such examples include.

- NUTS, BOLTS & SCREWS
- SENSORS
- SPROCKETS & CHAINS
- FORGING DIES
- SPLINES & GEARS
- BATTERY POSTS
- GASKETS
- KEYWAYS & SHAFTS
- BRAKE CAMS & PINS
- CONVEYORS
- VALVE ASSEMBLIES
- SPARK PLUGS

ADVANTAGES

HUSKEY 577 is unlike conventional products on the market because the maximum blend of metallic solids, proprietary dry-film lubricants and anti-galling agents have been homogenized into a specially designed petroleum base grease which does not contain clay or soap base thickeners. This helps to provide a superior product that will not melt and run out after application. In addition, this stable blend is unaffected by severe temperatures, vibration, expansion and contraction. Other advantages include:

- PROTECTS TO +1600 °F.
- REDUCES TORQUE
- PREVENTS CARBON FUSION
- PREVENTS RUST & CORROSION
- EXCELLENT LUBRICITY
- COMPATIBLE WITH STAINLESS STEEL
- PREVENTS GALLING & SEIZING
- STEAM & WATER RESISTANT
- CHEMICAL RESISTANT
- EXTREME PRESSURE LUBRICANT
- NON-MELTING



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:
1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:
8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE

* PRODUCT INFORMATION *

TYPICAL PROPERTIES

DESCRIPTION

HUSKEY Product:	577 Anti-seize
Color:	Silver Grey
Base Oil	Petroleum
Thickener	Synthetic
Texture	Buttery

<u>TESTS</u>	<u>ASTM TEST METHOD</u>	<u>RESULTS</u>
N.L.G.I. Grade	-----	1
Penetration		
Worked 60 strokes		320
Base Oils Viscosity,		
cSt @ 40°C	D-445	221
cSt @ 100°C	D-445	18
Pour Point, °F	D-97	15
Flash Point °F	D-92	420
Dropping Point °F	D-566	None

PACKAGE AVAILABILITY

1 gal. Pails, 5 gal. Pails, 15 gal. Keg and 55 gal. Drum
(Custom Packaging Available on Request)

CAUTION: Do Not Use On Oxygen Systems

The name of this product or group of products is for product identification only. HUSK-ITT Corp. makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT Corp. sales personnel are not authorized to amend this warranty limitation
07/16



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:
1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:
8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE