

* PRODUCT INFORMATION *

HUSKEY™ C-70-XL **ANTI-SEIZE COMPOUND FOR** **ROCK DRILL STEEL JOINTS AND COUPLINGS**

DESCRIPTION

HUSKEY C-70-XL is designed for rock drill steel joints and couplings used in "rope socket" percussion drilling operations. This product contains a high percentage of metallic powdered zinc homogenized into a superior grease carrier containing extreme pressure additives, rust and oxidation inhibitors.

USAGE

HUSKEY C-70-XL is a specialty product made primarily for use in the mining industry for percussion drilling.

ADVANTAGES

HUSKEY C-70-XL assures complete protection against extreme vibrations due to percussion impact. Will not melt or coke up. Performs under the most adverse conditions.

SERVICE RATING

0EF (-18EC) to 644EF (340EC).

OPERATING RANGE

Base grease provides lubrication to 450EF (232EC). Lubricating solids to 700EF (371EC).

TYPICAL SPECIFICATIONS

Base Thickener	Synthetic
Base Oil Viscosity,	
SUS @ 100EF	994
SUS @ 210EF	66
Worked Penetration	290-310
Dropping Point, EF (ASTM D-566)	None
Flash Point, EF (ASTM D-92)	430
Pour Point, EF (ASTM D-97)	0
Brushability (minimum), EF	15

PACKAGE AVAILABILITY

1 gal. Pail, 2 gal. Pail, 3½ gal. Pail and 5 gal. Pail

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation. 4/04



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE