

* PRODUCT INFORMATION *

HUSKEY™ CHAIN & CABLE LUBE

DESCRIPTION

HUSKEY CHAIN & CABLE LUBE is a transparent, heavy-duty dry film lubricant that cleans, penetrates and lubricates. It is formulated with the latest synthetic additives to assure maximum penetration and protection against rust and corrosion. When applied, the carrier solvent quickly evaporates, leaving behind a wax-like extreme pressure lubricant which will not wash-off or attract dust.

USAGE

HUSKEY CHAIN & CABLE LUBE was formulated to lubricate, preserve and protect not only chains and cables but as an excellent extreme pressure lubricant for all bearings and sliding surfaces. It is designed to fit a wide variety of industrial, agricultural, marine, automotive and household applications, such as:

- CHAIN AND CABLES
- CONVEYOR BEARINGS
- NUTS AND BOLTS
- CUTTING BLADES
- CHAIN SAWS
- SLIDING DOORS AND WINDOWS
- BUSHINGS AND SHAFTS
- DRAGLINES
- LOCKS AND HINGES
- GUNS

ADVANTAGES

- NON-STAINING
- DISPLACES MOISTURE
- CLEANS & LUBRICATES
- REDUCES WEAR
- WATERPROOF
- CHEMICAL RESISTANT
- PREVENTS RUST & CORROSION
- WILL NOT ATTRACT DIRT

CAUTION: Contains solvents which may affect certain plastics and rubbers; test thoroughly before use.

PACKAGE AVAILABILITY

16 fl. oz. (11 oz. net) Aerosol Cans (12 cans per case)
1 gal. Can (4/case), 5 gal. Pail, 15 gal. Keg, 55 gal. Drum



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE

* PRODUCT INFORMATION *

TYPICAL SPECIFICATIONS

<u>DESCRIPTION</u>	HUSKEY Product:	Chain & Cable Lube
	Color:	Light Amber
	Physical Form,	
	As Supplied:	Low Viscosity Liquid
	Without Solvent Carrier:	Thin Wax like Solid Film

<u>TEST</u>	<u>ASTM TEST METHOD</u>	<u>RESULTS</u>
Base Carrier	-----	Petroleum Solvent
Flash Point, °F	D-92	230 (non-aerosol)
Coefficient of Friction	LFW-4	
Dynamic		0.077
Static		0.087
Falex Pin & Vee Block ft. lb., Pass	D-3233 (B)	1000
Salt Spray Corrosion (5% salt @ 100 hrs.)	B-117	No Rust
Humidity Cabinet Test (60 hrs @ 120°F)	D-1748	Pass

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation. 06/14



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:
1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:
8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE