

# \* PRODUCT INFORMATION \*

## HUSKEY™ COOLUBE 65 GREASE

### DESCRIPTION

**HUSKEY COOLUBE 65** is a high performance, low temperature grease designed for high speeds and moderate loads. **HUSKEY COOLUBE 65** is blended from the highest quality petroleum base stocks and selectively treated with rust, oxidation and anti-wear additives coupled with an extremely shear stable thickener system.

### USAGE

**HUSKEY COOLUBE 65** was designed to provide excellent lubrication, wet or dry, over a wide temperature range (-65°F to 300°F.) in a large variety of industries, including textile, food processing, agriculture, automotive, etc. **HUSKEY COOLUBE 65** meets the performance requirements of MIL-G-10924C and MIL-G-10924D

**COOLUBE 65** is recommended for all bearing surfaces including fan bearings, spindles, freezer bearings, electric tools, slides, conveyors, etc.

### ADVANTAGES

- Wide Temperature Range
- Excellent for High Speeds
- Extremely Resistant to Water
- Meets the Requirements of Mil -PRF-10924 C&D and Ford WSB-M1C163-D
- Prevents Rust and Corrosion
- Extreme Pressure Resistant
- Reduces Friction and Wear

### TYPICAL PROPERTIES

| <u>TEST</u>   | <u>ASTM TEST METHOD</u> | <u>RESULTS</u>     |
|---|-------------------------|--------------------|
| Color   | -----                   | Amber              |
| Thickener   | -----                   | Calcium 12 Hydroxy |
| N.L.G.I. Grade                                      | -----                   | 2                  |
| Worked Penetration,<br>60 Strokes                   | D-217                   | 265-295            |
| Base Oil Viscosity                                  | D-445                   |                    |
| cSt @ 40°C  |                         | 15.1               |
| cSt @ 100°C   |                         | 3.2                |
| Pour Point, °F                                      | D-97                    | -65                |
| Flash Point, °F                                     | D-92                    | 300                |
| Dropping Point, °F                                  | D-566                   | 300                |
| Oxidation Stability,<br>(100 hrs. @ 210°F) psi Loss | D-942                   | 5                  |
| Oil Separation, % Loss                              | D-1742                  | 5                  |
| Rust Test   | D-1743                  | Pass               |
| Timken OK Load, lbs.                                | D-2509                  | 45                 |

### PACKAGE AVAILABILITY

Convenient disposable gun loader 14oz. Cartridge,  
1 gal. pail, 5 gal. Pail, 15 gal. Keg and 55 gal. Drum

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

08/14



## HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

### Western Region Office:

1580 Industrial Avenue, Norco, California 92860  
(951) 340-4000 • Fax: (951) 340-4011  
(888) 4-HUSKEY • www.huskey.com

### Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056  
(330) 425-2567 • Fax: (330) 425-9637  
(800) 238-LUBE