

* PRODUCT INFORMATION *

HUSKEY™ ECO-LUBE EP 2 GREASE

DESCRIPTION

HUSKEY ECO-LUBE EP 2 GREASE is a blend of the finest quality USA grown natural seed oils available then treated with the most effective anti-oxidants, extreme pressure, anti-wear and anti-corrosion additives. PTFE is added to further enhance load capacity, and reduce friction. This unique blend, together with its synthetic shear stable thickening system, provides the maximum protection against friction, wear and corrosion. **HUSKEY ECO-LUBE EP 2 GREASE** is readily biodegradable and contains no ozone depleting chemicals, SARA Title 313 chemicals, heavy metals, greenhouse gases, chlorine, phenols, VOC's or Prop. 65 Chemicals. **HUSKEY BIOBASE EP LUBE** is also NSF H-1 *Registered, KOSHER and Halal approved, which gives it full acceptability for use in ALL areas where incidental food or potable water contact may occur. **HUSKEY BIOBASE EP LUBE** is the ultimate "Green" Grease.

USAGE

HUSKEY ECO-LUBE EP 2 GREASE is a truly multi-service grease for extended service under extremely high and low temperature conditions from -20°F to 500°F. **HUSKEY ECO-LUBE EP 2 GREASE** has proven to be a problem solving lubricant in a wide variety of industries and applications. Some such applications include all roller, sleeve and pillow block bearings, bushings, couplings, universal joints, and sliding surfaces where a multi-purpose or extreme pressure grease is required.

ADVANTAGES

- **REDUCES FRICTION & WEAR**
- **WIDE TEMPERATURE RANGE**
- **READILY BIODEGRADABLE**
- **RENEWABLE RESOURCE BASED**
- **NSF H-1 *REGISTERED**
- **KOSHER APPROVED**
- **HALAL APPROVED**
- **ADVANCED RUST AND CORROSION PROTECTION**
- **FORMULATED WITH PTFE**
- **NON MELTING**



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:
1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:
8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE

* PRODUCT INFORMATION *

TYPICAL PROPERTIES

DESCRIPTION	HUSKEY Product:	ECO-LUBE EP 2 GREASE
	Color:	Amber
	Base:	Vegetable Oil
	Solid Lubricant:	PTFE
	NSF/U.S.D.A. Rating:	* H-1

<u>Test</u>	<u>ASTM Method</u>	<u>Typical Results</u>
N.L.G.I. Grade	-----	2
Worked Penetration, 60 Strokes	D-217	265 - 295
Dropping Point, °F	D-566	None
Base Oil Viscosity, cSt @ 40°C	D-445	35.8
cSt @ 100°C	D-445	8.6
Viscosity Index	D-2270	203
Flash Point, °F	D-92	520
Pour Point, °F	D-97	-20
Corrosion Preventative Test	D-1743	Pass
Water Washout, % Loss	D-1264	0.57
4-Ball Wear Scar (75 °C, 40 Kg, 1 hr. @ 1200 rpm)	D-2266	0.4
Falex Pin and "V" Block, Pass Lbs.	D-3233A (Modified)	3000

PACKAGE AVAILABILITY

Convenient disposable gun-loader 14oz. Cartridges,
1-gal. Pails, 5-gal. Pails, 15-gal. Kegs, and 55-gal. Drums

* NSF H-1 Registration No. 142968

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

5/18



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE