

* PRODUCT INFORMATION *

HUSKEY™ **MOLY-GRAPH GREASE**

DESCRIPTION

HUSKEY MOLY-GRAPH Grease is blended from the highest quality selected paraffinic petroleum oils, polymers and shear stable synthetic thickeners available. Treated with the latest chemical E.P. additives, rust and oxidation inhibitors to provide lasting protection against friction, wear and corrosion. Graphite and Molybdenum Disulfide (MOLY) lubricating solids of precise sub-micron and micron size have been completely homogenized into the product to further enhance load capacity, improve metal surfaces and reduce friction. Its Polymer base helps the grease to stay put and seal out dirt, water and other contaminants.

USAGE

HUSKEY MOLY-GRAPH Grease is a heavy duty, multi-service grease designed for all moderate to high speed plain, journal and anti-friction bearings operating in adverse conditions and over a wide temperature range from 5°F to a maximum intermittent temperature of 525°F. **HUSKEY MOLY-GRAPH Grease** was designed for a wide variety of industrial, automotive, mining, construction and agricultural applications such as wheel bearings, fans, conveyors, off highway equipment, kiln cars, roller chains, trunnions, gears, spindles, guide rails, pumps, cranes or other surfaces subjected to sliding, vibration or oscillation where fretting conditions are encountered.

ADVANTAGES

- Wide Temperature Range
- Extreme Pressure Protection
- Extends Equipment Life
- Multi-Purpose Grease
- Extremely Water Resistant
- Non Melting Formula
- Prevents Rust and Corrosion
- Excellent Pumpability

TYPICAL PROPERTIES

N.L.G.I. Grade	2	Oil Viscosity	
Worked Penetration	265-295	cSt @ 40°C	109
Base Thickener	Synthetic	cSt @ 100°C	12
Color	Black	Timken OK Load, Lbs.	45
Dropping Point, °F	None	Solid Lubricant	MolybdenumDisulfide,
Flash Point, °F	525		Amorphous Graphite
Pour Point, °F	5		

PACKAGE AVAILABILITY

Convenient disposable gun-loader 14 oz. Cartridges, 1 gal. Pail, 5 gal. Pail, 15 gal. Keg and 55 gal. Drum

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.
07/16



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE