

# \* PRODUCT INFORMATION \*

## HUSKEY™ N-500 SERIES OILS

### DESCRIPTION

**HUSKEY N-500 SERIES OILS** are a blend of highest quality selected paraffinic base oils coupled with the finest rust and oxidation resistant additives available. This unique combination produces an exceptional lubricating oil with excellent thermal stability and low carbon forming characteristics. Formulated with only high-viscosity index oils to minimize viscosity changes during high and low temperature variations. These oils have extremely high film strength, to keep working metal parts separated, thus reducing friction and wear. Compounded to meet service requirements of Denison HF-2 and Cincinnati Milicrons high temperature heat stability test.

### USAGE

**HUSKEY N-500 SERIES OILS** were designed primarily for all types of Air Compressors requiring non-detergent oils. These versatile oils are offered in several viscosity grades to meet the different needs of reciprocating, centrifugal and rotary compressors. Because of their anti-wear, anti-foam and excellent stability characteristics, they show outstanding performance when used as turbine oils, drip oils, hydraulic oils or general purpose lubricating oils.

### ADVANTAGES

- Minimal Viscosity Change at Operating Temperatures
- Rust and Oxidation Protection
- Low Carbon Forming
- Compatible with Sealants and Painted Surfaces
- High Film Strength
- Reduces Friction and Wear
- Extends Equipment Life

### TYPICAL PROPERTIES

<u>TEST</u>	<u>ASTM METHOD</u>	<u>RESULTS</u>		
ISO Grade	----	32	68	100
Pour Point, °F	D-97	-33	-25	-21
Flash Point, °F	D-92	432	475	502
Viscosity, cSt @ 40°C	D-445	32	68	100
Viscosity, cSt @ 100°C	D-445	5.2	8.3	10.8
Viscosity Index	----	90	90	95
Foam Tendency, ml, Seq. I, II, III	D-892	0/0/0	0/0/0	0/0/0
Rust Test	D-665	Pass	Pass	Pass

### PACKAGE AVAILABILITY

1 gal. Jugs (4/case), 5 gal. Pails, 15 gal. Kegs and 55 gal. Drums

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

07/16



## HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

### Western Region Office:

1580 Industrial Avenue, Norco, California 92860  
(951) 340-4000 • Fax: (951) 340-4011  
(888) 4-HUSKEY • www.huskey.com

### Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056  
(330) 425-2567 • Fax: (330) 425-9637  
(800) 238-LUBE