

# MOLYDUVAL

## Aladin FC Spray

### PTFE Dry Lubricant

An effective dry lubricant for applications under extreme conditions such as high pressures or high temperatures. It is suitable for dry lubrication as well as for adding it to liquid or greasy lubricants.

#### Properties

- \* provides good protection against corrosion
- \* reduces wear and friction
- \* very good tackiness
- \* low friction coefficient
- \* rejects dirt

#### Applications

- \* as separating agent in metal casting, die casting, forging, pressing
- \* for hydraulics in sensitive areas, for locks, weirs, sewage plants
- \* as sliding agent for wood
- \* as separating agent for soft plastics
- \* for preservation of battery poles
- \* for coating plastics

#### Technical Datas

Color		weiss
Temperature Range	°C	-180 -> +240
Basis		PTFE
Unit	ml	400

*The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.*

For more technical information contact us !

The technical data in this information sheet represents our present knowledge and is based on our general experience. It is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary tests with the selected product. It does also not form part of any sales contract as guaranteed properties of the delivered material.