

MOLYDUVAL Phoenix M 22



Pneumatic Tool Lubricant

Lubricant especially developed to meet the lubrication requirements of pneumatic tools.

This lubricant can be used in air-hoses or micro-fog lubricators for lubrication of hammers, pile-drivers, drills, grinders, pumps, hoists, clamps and vices.

Properties

- * relative good compatible with elastomers and seals
- * very good tackiness
- * absorbs moisture droplets on, provides anti-icing
- * free of acids

Applications

- * in air-hoses or micro-fog lubricators for lubrication of hammers, chisels, pile-drivers, drills, grinders, pumps, hoists, clamps and vices
- * for pneumatics

Technical Datas

Pour point	°C	-32
Density 15°C	kg/m ³	875
Viscosity 40°C	mm ² /s	22
Flash Point	°C	210

For further information, please see our website www.molyduval.com or consult your local representative.

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence.