

MOLYDUVAL Syntholube T Spray



Biodegradable Lubrication Spray

A light colour penetrating and lubrication oil with PTFE. Special usable for lubricating and preserving tools, screws, machine, chains. Contains the solid lubricant PTFE for reducing friction.

Properties

- * oxidation resistant
- * relative good compatible with elastomers and seals
- * good penetration
- * infiltrates water
- * looses dirt and residues
- * free of silicones
- * provides protection against corrosion
- * excellent tackiness

Applications

- * for instruments in precision engineering
- * for lubrication and preservation of machine parts, screws, valves, nuts, bolts, springs, hinges, locks, etc.
- * for protection of tools and instruments in storage
- * for cleaning engines, motors, steering
- * as water displacing agent for accu, contacts, controls, switches
- * for cleaning tools and machines
- * for sleeve bearing in electronics, CD players
- * for plain bearings in precision engineering, music and household equipment
- * for cleaning inox containers and machines
- * for chains in textile industry

Technical Datas

Color		white
Base Fluid		KW
Density 20°C	kg/m ³	800
Viscosity Base Fluid, 40°C	mm ² /s	22
Temperature Range	°C	-10 -> +100
Temperature Range solid lubrication	°C	-180 -> +260
Content additives	%	PTFE
Fineness Ø	µm	< 6

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.

For further information, please see our website www.molyduval.com or consult your local representative.

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence.