

ROYCO[®] 756 & ROYCO 756A

HYDRAULIC FLUID, AIRCRAFT,
MISSILE, AND ORDINANCE PETROLEUM BASE

Description

ROYCO 756 is a red-dyed, mineral oil based hydraulic fluid developed for the severe duty demands of aerospace and industrial service. **ROYCO 756** contains additives that provide excellent low temperature fluidity as well as exceptional anti-wear, oxidation / corrosion inhibition, and shear stability. In addition, metal deactivators and foam inhibitors are provided in this high viscosity index fluid to enhance performance in many general purpose hydraulic applications

Applications

ROYCO 756 is designed for use in aircraft, missiles, autopilots, shock absorbers, cherry pickers, boom trucks, robotics, and auto wreckers requiring all-weather performance. **ROYCO 756** is particularly recommended for use in systems where a "super clean" fluid can contribute to improved component life and reliability. **ROYCO 756** can be used in unpressurized systems operating at temperature ranges from -54 to 90°C (-65 to 195°F) and in pressurized systems from -54 to 135°C (-65 to 275°F) at pressures up to 3000 psi. **ROYCO 756A** may be used in systems not requiring a "super clean" ID and where the convenience of a re-sealable container can provide cost savings.

Features and Benefits

- Wide operating temperature range
- Low temperature fluidity
- Exceptional anti-wear performance
- "Super Clean" Fluid to improve equipment life
- Excellent oxidation and corrosion inhibition

Approvals and Specifications

ROYCO 756 meets all requirements and is qualified under MIL-SPEC: MIL-PRF-5606H(3) that supersedes Mil-H-5606G, Mil-O-5606, AN-O-336, AN-VV-O-336, and AAF-3580.

ROYCO 756A meets the technical requirements of Mil-H-5606A.

TYPICAL PROPERTIES	TEST METHOD	ROYCO® 756
Kinematic Viscosity, cSt		
@ 100°C	ASTM D445	5.28
@ 40°C	ASTM D445	14.30
@ -40°C	ASTM D445	473
@ -54°C	ASTM D445	2028
Low Temperature Stability, -54°C, 72 hours	FTM 3458	pass
Pour Point, °C	ASTM D97	-62
Flash Point, COC, °F	ASTM D92	231
Acid Number, mq KOH/g	ASTM D664	.04
Density, pounds per gallon	ASTM D287	7.261
Copper Corrosion, 135°C, 72 hours, ASTM color	ASTM D130	1B
Water Content, ppm	ASTM D6304	44.9
4-Ball Wear, 75°C, 40 kg, 1200 rpm, 1 hour, mm	ASTM D4172	.58
Evaporation, 71°C, 6 hours, %wt loss	ASTM D972A	10.4
Gravimetric Filtration mg/100 ml, 0.45µ @ 25°C	Para 4.4.3	
Barium Content, ppm	ASTM D5185	1
Foam Resistance, 75°F	ASTM D892	
foam volume, ml		32
foam stability		none
API Gravity	ASTM D4052	30.8
Micron Size, count / mL		
5-15 µm	FTM 3012	963
16-25 µm	FTM 3012	120
26-50 µm	FTM 3012	36
51-100 µm	FTM 3012	5
100+ µm	FTM 3012	1
Water, Coulometric KF Titration, ppm	ASTM D6304	45

The information contained herein relates to a specific Chemtura product and its use, and is based on information available as of the date hereof. Additional information relating to the product can be obtained from the pertinent Material Safety Data Sheets. Nothing in this Technical Data Sheet constitutes a term or condition of sale nor shall it take precedence over, supersede or modify or be construed to take precedence over, supersede or modify, any of Chemtura's standard or other terms and conditions of sale under which the product is sold by Chemtura. NOTHING IN THIS TECHNICAL DATA SHEET CONSTITUTES, NOR SHALL IT BE CONSTRUED TO CONSTITUTE, A REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, REGARDING THE PRODUCT'S CHARACTERISTICS, USE, QUALITY, SAFETY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall constitute permission or recommendation to practice any intellectual property without the permission of the owner. This product is sold only under terms and conditions agreed in writing by Chemtura and the respective buyer and the terms and conditions of such agreements shall in all cases prevail. ANDEROL, ROYCO, AOSyn and PQ and their corresponding logos are trademarks of Chemtura Corporation or one of its subsidiaries. Copyright (c) 2010 Chemtura Corporation. All rights reserved.



Anderol Specialty Lubricants
a division of Chemtura Corporation
215 Merry Lane
East Hanover, New Jersey 07936
Technical Service +1.973.887.7410
Customer Service +1.203.573.4595
Fax +1.203.573.2324
info-anderol@chemtura.com
www.anderol.com

TYPICAL PROPERTIES	TEST METHOD	ROYCO® 756A
Pour Point, °C	ASTM D97	- 63
Flash Point, COC, °F	ASTM D93	231
Acid Number, mq KOH/g	ASTM D664	.04
Density, pounds per gallon	ASTM D287	7.26
Kinematic Viscosity, cSt		
@ 130°F	ASTM D445	10.6
@ -40°F	ASTM D445	467

Packaging

ROYCO 756 is available in 55-gallon drum, 5-gallon pail, 24 x 1-Qt case and 6 x 1-gallon case.

ROYCO 756A is available in 6 x 1 gallon cases. Other package sizes may be available on special request.

Limitations

ROYCO 756 should not be used in systems using natural rubber elastomers.

The information contained herein relates to a specific Chemtura product and its use, and is based on information available as of the date hereof. Additional information relating to the product can be obtained from the pertinent Material Safety Data Sheets. Nothing in this Technical Data Sheet constitutes a term or condition of sale nor shall it take precedence over, supersede or modify or be construed to take precedence over, supersede or modify, any of Chemtura's standard or other terms and conditions of sale under which the product is sold by Chemtura. NOTHING IN THIS TECHNICAL DATA SHEET CONSTITUTES, NOR SHALL IT BE CONSTRUED TO CONSTITUTE, A REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, REGARDING THE PRODUCT'S CHARACTERISTICS, USE, QUALITY, SAFETY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall constitute permission or recommendation to practice any intellectual property without the permission of the owner. This product is sold only under terms and conditions agreed in writing by Chemtura and the respective buyer and the terms and conditions of such agreements shall in all cases prevail. ANDEROL, ROYCO, AOSyn and PQ and their corresponding logos are trademarks of Chemtura Corporation or one of its subsidiaries. Copyright (c) 2010 Chemtura Corporation. All rights reserved.



Anderol Specialty Lubricants
 a division of Chemtura Corporation
 215 Merry Lane
 East Hanover, New Jersey 07936
 Technical Service +1.973.887.7410
 Customer Service +1.203.573.4595
 Fax +1.203.573.2324
 info-anderol@chemtura.com
www.anderol.com