

WOLFRAKOTE TOP FLUID, WOLFRAKOTE TOP FLUID S

Solid lubricant suspensions for high-temperature applications



Benefits for your application

- **For high temperatures up to approx. 1000°C**
- **Good wetting power**
- **Good penetrating properties**

Description

WOLFRAKOTE TOP FLUID and WOLFRAKOTE TOP FLUID S are suspensions containing solid lubricant based on mineral and hydrocarbon oils. Upon evaporation of the base oil at temperatures above 200°C the solid lubricants provide dry lubrication.

Application

WOLFRAKOTE TOP FLUID products are used for the lubrication of conveyor chains in tube annealing furnaces, continuous furnaces or stress-relieving ovens at temperatures > 250°C.

Application notes

WOLFRAKOTE TOP FLUID

Initial lubrication by brush. Relubrication by automatic metering systems. Recommended chain temperature for relubrication: 100 – 150°C

WOLFRAKOTE TOP FLUID S

Initial lubrication by immersion at the chain manufacturer. Relubrication by automatic metering systems. Recommended chain temperature for relubrication: < 100°C.

WARNING: WOLFRAKOTE TOP FLUID S contains a solvent. Keep away from sources of ignition and observe safety data sheet. To prevent solid lubricants from settling provide automatic metering systems with a stirrer.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Pack sizes	WOLFRAKOTE TOP FLUID	WOLFRAKOTE TOP FLUIDS
Canister 5 l	+	+
Bucket 25 l	+	-
Canister 1 l	-	+
Canister 5 l	+	+



WOLFRAKOTE TOP FLUID, WOLFRAKOTE TOP FLUID S

Solid lubricant suspensions for high-temperature applications

Product data	WOLFRAKOTE TOP FLUID	WOLFRAKOTE TOP FLUIDS
Article number	985003	985004
Runout time, DIN EN ISO 2431, with flow cups, nozzle 6 mm		approx. 45 s
Chemical composition	solid lubricant	solid lubricant
Chemical composition, solvent		hydrocarbon
Chemical composition, type of oil	synthetic hydrocarbon oil	synthetic hydrocarbon oil
Chemical composition, type of oil	mineral oil	mineral oil
Density at 20 °C	approx. 1.12 g/cm ³	approx. 1.1 g/cm ³
Colour space	grey	grey
Upper service temperature	1000 °C / 1832 °F	1000 °C / 1832 °F
Lower service temperature	-25 °C / -13 °F	-25 °C / -13 °F
Texture	viscous	liquid
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	24 months	12 months

Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 80 years.

**Klüber Lubrication München SE & Co. KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.**

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München SE & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München SE & Co. KG and if source is indicated and voucher copy is forwarded.



a company of the Freudenberg Group