

# RUST VETO 4240

## Data Sheet

RUST VETO 4240 is a new solvent based rust preventive that rapidly displaces and separates water. The product exhibits a very thin, dry to touch film which, if applied properly, offers up to one year of indoor rust protection. Extremely low odour properties make this product very operator friendly.

### FEATURES:

- Low odour
- Excellent humidity rust protection
- Exceptionally dry to touch film
- High flash 90.56°C
- Displaces water
- Fast water separation
- Easily removed
- For use with all metals
- Barium-free
- Low freeze and pour point
- Reduced drag-out

### TYPICAL PHYSICAL AND PROTECTIVE PROPERTIES

Appearance	Clear amber
Specific gravity	0.79
Copper corrosion ASTM D-130	1a
Flash point, PMCC	70 C°
Film thickness	0.36 mls
Film type	Dry touch film
Water displacement	Passes
Water separation	Passes
Humidity @ 120°F/100% RH polished Panels	Passes 30+days

## APPLICATIONS

RUST VETO 4240 can be applied through specific drip, by immersion, by brush, through electrostatic device or sprayed. (On rolling machines the product is directly sprayed on working rolls).

RUST VETO 4240 is supplied in drums (180 kilos) or bulk (packages 1.000 kilos about )

## HEALTH & SAFETY

No toxic or carcinogenic, teratogenic or mutagenic known materials are contained in RUST VETO 4240 such as nitrosamines, phenols, polychlorinated diphenyl, heavy metals, polinuclear hydrocarbons.

## STORAGE

RUST VETO 4240 maintains its chemical-physical and technical characteristics if stored in a sheltered place at a temperature of  $-5^{\circ}\text{C}$  and  $+40^{\circ}\text{C}$  maximum for a period of twelve months.

## WASTE TREATMENT

RUST VETO 4240 cannot be directly discharged. Follow national or local instructions.

N/02 -X02169-APPROVAL : D. PETTAI