

**TURMOPLEX 2 EP**

Issued: 11.08.2003

K P 2 K -30

**LUBCON - Universal Grease**

LUBCON-Universal Grease **TURMOPLEX 2 EP** has been produced with selected raw materials and special additives. It is transparent and natural-coloured. The consistency is medium to soft with smooth texture.

LUBCON-Universal Grease **TURMOPLEX 2 EP** has a wide temperature range and guarantees excellent service life because of its special oxidation stability.

LUBCON-Universal Grease **TURMOPLEX 2 EP** has an optimum water resistance and excellent corrosion protection. Allows therefore lubrication at humid conditions without problems.

**Technical Data**

**TURMOPLEX 2 EP**

Temperature range short time	-30°C to +120°C +130°C
Dropping point according DIN ISO 2176	> 180°C
Thickener	Lithium
Base oil	Mineral oil
Base oil viscosity DIN 51562 at 40°C	approx. 150 mm <sup>2</sup> /s
Consistency class DIN 51818	2
Worked penetration DIN ISO 2137	265 - 295
Corrosion protection ( Emcor) DIN 51802	0 - 0
SKF running test DIN 51806	up to +130°C passed
Four-ball test value (VKA) DIN 51350	2800 N / 3000 N
Pumpability by means of	grease presses, automatical lubrication devices, central lubricating systems

**USES**

LUBCON-Universal Grease **TURMOPLEX 2 EP** can be used for lubrication of roller and friction bearings, for normal to high temperatures, for high and low speeds, as universal grease for cars, industrial machines, machines for the construction industry or similar.